

# STRING WAVES

## GENERAL EQUATION OF WAVE MOTION :

$$\frac{\partial^2 y}{\partial t^2} = v^2 \frac{\partial^2 y}{\partial x^2}$$

$$y(x,t) = f\left(t \pm \frac{x}{v}\right)$$

where,  $y(x, t)$  should be finite everywhere.

$\Rightarrow f\left(t + \frac{x}{v}\right)$  represents wave travelling in -ve x-axis.

$\Rightarrow f\left(t - \frac{x}{v}\right)$  represents wave travelling in +ve x-axis.

$$y = A \sin(\omega t \pm kx + \phi)$$

## TERMS RELATED TO WAVE MOTION ( FOR 1-D PROGRESSIVE SINE WAVE )

**(e) Wave number (or propagation constant) (k) :**

$$k = 2\pi/\lambda = \frac{\omega}{v} \text{ (rad m}^{-1}\text{)}$$

**(f) Phase of wave :** The argument of harmonic function  $(\omega t \pm kx + \phi)$  is called phase of the wave.

Phase difference  $(\Delta\phi)$  : difference in phases of two particles at any time  $t$ .

$$\Delta\phi = \frac{2\pi}{\lambda} \Delta x \quad \text{Also, } \Delta\phi = \frac{2\pi}{T} \cdot \Delta t$$

## SPEED OF TRANSVERSE WAVE ALONG A STRING/WIRE.

$$v = \sqrt{\frac{T}{\mu}} \quad \text{where } \begin{array}{l} T = \text{Tension} \\ \mu = \text{mass per unit length} \end{array}$$

## POWER TRANSMITTED ALONG THE STRING BY A SINE WAVE

$$\text{Average Power } \langle P \rangle = 2\pi^2 f^2 A^2 \mu v$$

$$\text{Intensity } I = \frac{\langle P \rangle}{s} = 2\pi^2 f^2 A^2 \rho v$$

## REFLECTION AND REFRACTION OF WAVES

$$y_i = A_i \sin(\omega t - k_1 x)$$

$$\left. \begin{array}{l} y_t = A_t \sin(\omega t - k_2 x) \\ y_r = -A_r \sin(\omega t + k_1 x) \end{array} \right] \text{ if incident from rarer to denser medium } (v_2 < v_1)$$



$$\left. \begin{aligned} y_t &= A_t \sin(\omega t - k_2 x) \\ y_r &= A_r \sin(\omega t + k_1 x) \end{aligned} \right\} \text{if incident from denser to rarer medium. } (v_2 > v_1)$$

(d) Amplitude of reflected & transmitted waves.

$$A_r = \frac{|k_1 - k_2|}{k_1 + k_2} A_i \quad \& \quad A_t = \frac{2k_1}{k_1 + k_2} A_i$$

### STANDING/STATIONARY WAVES :-

$$\begin{aligned} (b) \quad y_1 &= A \sin(\omega t - kx + \theta_1) \\ y_2 &= A \sin(\omega t + kx + \theta_2) \end{aligned}$$

$$y_1 + y_2 = \left[ 2A \cos\left(kx + \frac{\theta_2 - \theta_1}{2}\right) \right] \sin\left(\omega t + \frac{\theta_1 + \theta_2}{2}\right)$$

The quantity  $2A \cos\left(kx + \frac{\theta_2 - \theta_1}{2}\right)$  represents resultant amplitude at  $x$ . At some position resultant amplitude is zero these are called **nodes**. At some positions resultant amplitude is  $2A$ , these are called **antinodes**.

$$(c) \text{ Distance between successive nodes or antinodes} = \frac{\lambda}{2}.$$

(d) Distance between successive nodes and antinodes =  $\lambda/4$ .

(e) All the particles in same segment (portion between two successive nodes) vibrate in same phase.

(f) The particles in two consecutive segments vibrate in opposite phase.

(g) Since nodes are permanently at rest so energy can not be transmitted across these.

### VIBRATIONS OF STRINGS ( STANDING WAVE)


(a) Fixed at both ends :

1. Fixed ends will be nodes. So waves for which


$$L = \frac{\lambda}{2}$$



$$L = \frac{2\lambda}{2}$$



$$L = \frac{3\lambda}{2}$$



are possible giving

$$L = \frac{n\lambda}{2}$$


$$\text{or } \lambda = \frac{2L}{n} \text{ where } n = 1, 2, 3, \dots$$

$$\text{as } v = \sqrt{\frac{T}{\mu}}$$

$$f_n = \frac{n}{2L} \sqrt{\frac{T}{\mu}}, \quad n = \text{no. of loops}$$

**(b) String free at one end :**

1. for fundamental mode  $L = \frac{\lambda}{4}$  = or  $\lambda = 4L$



First overtone  $L = \frac{3\lambda}{4}$  Hence  $\lambda = \frac{4L}{3}$



so  $f_1 = \frac{3}{4L} \sqrt{\frac{T}{\mu}}$  (First overtone)

Second overtone  $f_2 = \frac{5}{4L} \sqrt{\frac{T}{\mu}}$

so  $f_n = \frac{\left(n + \frac{1}{2}\right)}{2L} \sqrt{\frac{T}{\mu}} = \frac{(2n+1)}{4L} \sqrt{\frac{T}{\mu}}$